



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : <b>H01T 1/14, H01C 7/12</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 99/08353</b></p> <p>(43) International Publication Date: 18 February 1999 (18.02.99)</p>
<p>(21) International Application Number: <b>PCT/US98/11099</b></p> <p>(22) International Filing Date: 1 June 1998 (01.06.98)</p> <p>(30) Priority Data:              08/907,327      6 August 1997 (06.08.97)      US              08/954,987      21 October 1997 (21.10.97)      US</p> <p>(71) Applicant: <b>JOSLYN MANUFACTURING CO. [US/US]; 3700 South Morgan Street, Chicago, IL 60609 (US).</b></p> <p>(72) Inventor: <b>HENSLEY, Steven, P.</b></p> <p>(74) Agent: <b>JOIKE, Trevor, B.; Marshall, O'Toole, Gerstein, Murray &amp; Borun, 6300 Sears Tower, 233 South Wacker Drive, Chicago, IL 60606 (US).</b></p>		<p>(81) Designated States: <b>BR, CA, CN, ID, JP, KR, MX, SG, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</b></p> <p><b>Published</b>  <i>With international search report.</i></p>
<p>(54) Title: <b>SURGE ARRESTER HAVING DISCONNECTOR HOUSED BY END CAP</b></p> <p>(57) Abstract</p> <p>An apparatus includes a surge arresting element, first and second end caps, an arrester housing, and a fault disconnecter. The surge arresting element is arranged to conduct in the presence of the surge on a power line. The first and second end caps are arranged to be electrically connected to the surge arresting element, and the second end cap forms a disconnecter housing. The arrester housing is arranged to house the surge arresting element and the first and second end caps so that the disconnecter housing is accessible from an exterior of the arrester housing. The fault disconnecter is arranged to electrically disconnect the surge arresting element from the power line in the event of a fault, and the fault disconnecter is housed within the disconnecter housing formed by the second end cap. A fastener is arranged to fasten the surge arresting element, the first and second end caps, the arrester housing, and the fault disconnecter to a mounting bracket so as to wedge the arrester housing between the mounting bracket and the second end cap in order to form a seal.</p> <div data-bbox="824 1142 1386 1940"> </div>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

SURGE ARRESTER HAVING DISCONNECTOR HOUSED BY END CAPRelated Application

This application is a continuation-in-part of  
U.S. Application Serial No. 08/907,327 filed on August 6,  
1997.

5

Technical Field of the Invention

The present invention relates to a surge arrester for shunting electrical surges to ground. More particularly, the surge arrester of the present invention may have a disconnect which disconnects the surge arrester from ground in the event of a failure of the surge arrester.

10

Background of the Invention

Overvoltage surges, which travel along an electric power distribution system and which are not properly averted or diverted, often damage transformers and other electrical equipment of the electric power distribution

15

system, as well as the electrical equipment of residential, commercial and industrial customers supplied by the electric power distribution system. Consequently, surge arresters are commonly used in an electric power distribution system for shunting overvoltage surges to system ground before the overvoltage surges can damage the electrical equipment connected in, or to, the electric power distribution system.

Typical surge arresters used in electric power distribution systems can fail in a runaway condition. When such a failure occurs, the surge arrester may explode apart, potentially damaging nearby equipment and injuring anyone who happens to be near. Therefore, it has been a common prior art practice to provide surge arresters with fault disconnectors which open the circuits containing failed surge arresters. Usually, a fault disconnector is connected between its corresponding surge arrester and ground so that, when the fault disconnector activates upon failure of the surge arrester, the fault disconnector separates the surge arrester from its ground connection. The separated ground connection not

only disconnects the failed surge arrester from the electric power distribution system, but also provides a visible indication to a utility linesmen that the surge arrester has failed.

5                   A typical fault disconnecter includes a cartridge, which may contain a predetermined amount of gun powder, and which is heated as the surge arrester begins to fail. When the cartridge heats sufficiently, it explodes separating the surge arrester from its ground  
10 connection. The amount of gun powder that is used in the cartridge is sufficient to cause such separation but not sufficient to cause damage or injury.

                  The cartridge, and the other elements of the fault disconnecter, are contained within a disconnecter  
15 housing that is a separate component of the surge arrester, that has an internally threaded hole for threaded attachment to a housing of the surge arrester, and that has an external threaded ground connector for attachment to a ground lead. An electrical resistor, which is an-  
20 other element of the fault disconnecter and which is housed by the disconnecter housing, is electrically

connected between a surge arrester terminal and the ground connector of the disconnecter. Accordingly, when the surge arrester fails, the current through the electrical resister increases abnormally and generates enough heat to trigger the cartridge causing it to break the disconnecter housing and to separate the ground terminal from the surge arrester.

The use of a separate disconnecter housing increases the part count of a surge arrester which, in turn, increases the manufacturing cost of the surge arrester. The present invention is directed to a surge arrester which reduces part count.

#### Summary of the Invention

In accordance with one aspect of the present invention, a surge arrester comprises a surge arresting element, first and second end caps, and a fault disconnecter. The surge arresting element is arranged to conduct in the presence of a surge. The first end cap is arranged to electrically connect the surge arresting element to a first electrical line. The second end cap is

electrically connected to the surge arresting element and forms a disconnecter housing. The fault disconnecter is arranged to electrically connect the second end cap to a second electrical line, the fault disconnecter is arranged to disconnect the surge arresting element from the second electrical line in the event of a fault, and the fault disconnecter is housed within the disconnecter housing formed by the second end cap.

In accordance with another aspect of the present invention, an apparatus for arresting a surge on a power line comprises a surge arresting element, first and second end caps, an arrester housing, and a fault disconnecter. The surge arresting element is arranged to conduct in the presence of the surge on the power line. The first end cap is arranged to electrically connect the surge arresting element to a first electrical line. The second end cap is electrically connected to the surge arresting element, and the second end cap forms a disconnecter housing. The arrester housing is arranged to house the surge arresting element and the first and second end caps. The fault disconnecter is arranged to

connect the second end cap to a second electrical line,  
the fault disconnecter is arranged to disconnect the  
surge arresting element from the second electrical line  
in the event of a fault, and the fault disconnecter is  
5 housed within the disconnecter housing formed by the  
second end cap.

In accordance with yet another aspect of the  
present invention, a surge arrester comprises arrester  
elements, an arrester housing, a mounting bracket, and a  
10 fastener. The arrester elements are arranged to conduct  
in the event of a surge. The arrester housing houses the  
arrester elements. The mounting bracket supports the ar-  
rester elements and the arrester housing. The fastener  
clamps the arrester elements and the arrester housing to  
15 the mounting bracket so that the arrester housing is  
wedged between the mounting bracket and the arrester  
elements in order to form a seal for the arrester ele-  
ments.

In accordance with a further aspect of the  
20 present invention, a surge arrester comprises a plurality  
of surge arresting elements, an arrester housing, and a



fault disconnecter. A first of the surge arresting elements is arranged to be electrically connected to a first electrical line, a second of the surge arresting elements is arranged to conduct in the presence of a surge, and a  
5 third of the surge arresting elements forms a disconnecter housing. The arrester housing is arranged to house the plurality of surge arresting elements so that the disconnecter housing is accessible from an exterior of the arrester housing. The fault disconnecter is arranged to electrically connect the third of the surge  
10 arresting elements to a second electrical line, the fault disconnecter is arranged to disconnect the surge arresting elements from the second electrical line in the event of a fault, and the fault disconnecter is housed within  
15 the disconnecter housing.

In accordance with a still further aspect of the present invention, a surge arrester comprises arrester elements, an arrester housing, a mounting bracket, and a threadless fastener. The arrester elements are  
20 arranged to conduct in the event of a surge. The arrester housing houses the arrester elements. The mount-

ing bracket supports the arrester elements and the arrester housing. The threadless fastener is arranged to attach the arrester elements and the arrester housing to the mounting bracket so that the arrester elements and the arrester housing are supported by the mounting bracket.

In accordance with a yet further aspect of the present invention, a surge arrester comprises arrester elements, an arrester housing, and an electrically conductive connector. The arrester elements are arranged to conduct in the event of a surge. The arrester housing houses the arrester elements, and the arrester housing has an integrally formed O-ring. The electrically conductive connector cooperates with the integrally formed O-ring to form a seal between an interior of the arrester housing and an exterior of the arrester housing, and the electrically conductive connector is arranged to be electrically coupled to one of the arrester elements.

#### Brief Description of the Drawings

These and other features and advantages of the present invention will become more apparent from a detailed consideration of the invention when taken in conjunction with the drawings in which:

5               Figure 1 illustrates a first embodiment of a surge arrester that includes a fault disconnecter according to the present invention;

              Figure 2 is an exploded view of the fault disconnecter illustrated in Figure 1;

10             Figure 3 is an enlarged view of a second embodiment of a surge arrester according to the present invention;

              Figure 4 illustrates a third embodiment of a surge arrester according to the present invention; and,

15             Figure 5 illustrates a fourth embodiment of a surge arrester according to the present invention.

#### Detailed Description

As shown in Figure 1, a surge arrester 10 includes a first terminal end 12 and a second terminal end 14. The first terminal end 12 includes a first connector

20

16 which is used to electrically connect the surge arrester 10 to a first electrical line. The second terminal end 14 includes a second connector 18 which is used to electrically connect the surge arrester 10 to a second electrical line. The first electrical line may be, for example, an electrically conducting lead which connects the first connector 16 to a high voltage line of an electrical power distribution system, and the second electrical line may be an electrically conducting lead which connects the second connector 18 to ground. Alternatively, however, the first electrical line may be, for example, an electrically conducting lead which connects the first connector 16 to ground, and the second electrical line may be an electrically conducting lead which connects the second connector 18 to a high voltage line of an electrical power distribution system.

The first connector 16 is threaded into a first end cap 20, and the second connector 18 is electrically connected to a second end cap 22 in a manner to be described below. The first and second end caps 20 and 22 are electrically conductive and, for example, may be

formed from aluminum. A first surge arresting element 24 is in electrical contact with the first end cap 20, a second surge arresting element 26 is in electrical contact with the first surge arresting element 24, a third surge arresting element 28 is in electrical contact with the second surge arresting element 26, and a fourth surge arresting element 30 is in electrical contact with both the third surge arresting element 28 and the second end cap 22. Accordingly, a series circuit is formed between the first and second end caps 20 and 22. The surge arresting elements 24-30 may be metal oxide varistor blocks, for example, which conduct in the presence of surges in order to shunt the surge energy in the electric power distribution system between the first and second connectors 16 and 18.

An arrester housing 32 houses the first and second end caps 20 and 22 and the surge arresting elements 24, 26, 28, and 30. As is known, the arrester housing 32 may be an insulating polymeric or porcelain housing having a plurality of polymeric or porcelain water sheds 34. A mounting bracket 36 is provided in

order to mount and support the surge arrester 10 to a utility pole or other apparatus of an electric power distribution system.

As shown in Figures 1 and 2, the second end cap 22 has a first end 40 which is in electrical contact with the fourth surge arresting element 30. The second end cap 22 also has a second end 42 which comprises a wall 44 forming a recess 46. A fault disconnecter 47 includes a cartridge 48 which is contained within an end 50 of the second connector 18. The fault disconnecter 47 also includes a first electrically conductive washer 52 abutting the end 50 of the second connector 18, a second electrically conductive washer 54 abutting an internal wall 58 of the second end cap 22, and a resistor 56 sandwiched between the first and second electrically conductive washers 52 and 54. A plastic cup 59 contains the first and second electrically conductive washers 52 and 54 and the resistor 56 when the fault disconnecter 47 is assembled as shown in Figure 1. Thus, the plastic cup 59 insulates the resistor 56 and the first and second electrically conductive washers 52 and 54 from the wall

44 of the second end cap 22 forcing fault current to flow from the second end cap 22 through the second electrically conductive washer 54, through the resistor 56, through the first electrically conductive washer 52, and through the second connector 18.

The wall 44 of the second end cap 22 has a circumferential groove 60 therearound. During assembly of the surge arrester 10, the surge arresting elements 24, 26, 28, and 30 are stacked between the first and second end caps 20 and 22. The stack formed by the surge arresting elements 24, 26, 28, and 30 and the first and second end caps 20 and 22 is wrapped with a fiber glass weave in order to retain the surge arresting elements 24, 26, 28, and 30 and the first and second end caps 20 and 22 in the stack. The arrester housing 32 is applied to the wrapped stack of the surge arresting elements 24, 26, 28, and 30 and the first and second end caps 20 and 22 as shown in Figure 1. For example, the arrester housing 32 may be molded directly on the wrapped stack of the surge arresting elements 24, 26, 28, and 30 and the first and second end caps 20 and 22.

The arrester housing 32 is mounted to the mounting bracket 36 by inserting the wall 44 through an opening 62 in the mounting bracket 36 as shown in Figure

1. The mounting bracket 36 may have a first recess 64 and a second recess 66 which are concentric with respect to one another. The first recess 64 is formed by a generally cylindrical wall 68 of the mounting bracket 36.

The generally cylindrical wall 68 may have an internal taper. As the second end cap 22 is pushed through the opening 62 in the mounting bracket 36, a flange 70 of the second end cap 22 enters the second recess 66 of the mounting bracket 36, and the taper of the generally cylindrical wall 68 causes an end portion 72 of the arrester housing 32 to be squeezed between the generally cylindrical wall 68 and the flange 70 of the second end cap 22. As a result of this squeezing action, the end portion 72 acts as a gasket or seal at the second terminal end 14 in order to isolate the interior of the arrester housing 32 from the external environment. When the arrester housing 32 is fully pressed into the opening 62 of the mounting bracket 36 so that the circumferential



groove 60 is accessible, a snap ring 73 is snapped into the circumferential groove 60 in the wall 44 of the second end cap 22 to thereby clamp the surge arrester 10 to the mounting bracket 36 with enough force to maintain the seal by the end portion 72 between the generally cylindrical wall 68 and the flange 70 of the second end cap 22.

A subassembly 74 is formed by inserting the second connector 18, with the cartridge 48 inserted in the end 50, through the plastic cup 59 until the plastic cup 59 abuts a flange 76 at the end 50 of the second connector 18, and by inserting the first electrically conductive washer 52 into the plastic cup 59 until the first electrically conductive washer 52 abuts the flange 76 at the end 50 of the second connector 18. The resistor 56 is inserted into the plastic cup 59 until the resistor 56 abuts the first electrically conductive washer 52, and the second electrically conductive washer 54 is placed on top of the resistor 56. The subassembly 74 is then inserted into the recess 46 of the second end cap 22 until the second electrically conductive washer 54

abuts the internal wall 58, leaving a space 78 as shown in Figure 1. The space 78 is filled with an epoxy potting material in order to hold the subassembly 74 in electrical contact with the second end cap 22.

5                   Accordingly, the recess 46 in the second end cap 22 forms a disconnecter housing for the fault disconnecter 47 so as to eliminate the need for a separate housing for the fault disconnecter 47.

10                   Instead of using the snap ring 73 in the circumferential groove 60 of the second end cap 22 to clamp the first and second end caps 20 and 22, the surge arresting elements 24, 26, 28, and 30, and the arrester housing 32 to the mounting bracket 36, the second end cap 22 may be threaded into the mounting bracket 36. To this  
15                   end, the second end cap 22 may be externally threaded at a region 80 as shown in Figure 3.

20                   As shown in Figure 1, the arrester housing 32 is formed over the first end cap 20 so as to provide a seal in cooperation with a flange 90 of the first connector 16. This seal at the first terminal end 12 isolates the interior of the arrester housing 32 from the external

environment. Alternatively, the arrester housing 32 may be configured with an integral O-ring 92 as shown in Figure 4. The integral O-ring 92 fits within an annular groove 94 about a first end cap 20A in order to provide a seal at the first terminal end 12 that isolates the interior of the arrester housing 32 from the external environment.

Instead of configuring an integral O-ring according to the integral O-ring 92 shown in Figure 4, an integral O-ring 100 may be provided as shown in Figure 5. The integral O-ring 100 is integrally formed in the arrester housing 32 at its top and defines an opening 102 through which the first connector 16 extends so that it may be threaded into the first end cap 20. The integral O-ring 100 fits within an annular recess 104 formed in a flange 106 of the first connector 16. As the first connector 16 is threaded into the first end cap 20, the integral O-ring 100 is tightly squeezed into the annular recess 104 and cooperates with the flange 106 in order to provide a seal at the first terminal end 12 that isolates

the interior of the arrester housing 32 from the external environment.

Certain modifications of the present invention have been discussed above. Other modifications will occur to those practicing in the art of the present invention. For example, the first connector 16 and the first end cap 20 are shown as being separate elements. Instead, the first connector 16 and the first end cap 20 may be formed as a single, integrated, electrically conductive element.

Also, four surge arresting elements 24, 26, 28, and 30 are shown in Figure 1 as being electrically connected between the first and second end caps 20 and 22. However, any number of surge arresting elements may be provided between the first and second end caps 20 and 22 depending upon the voltage carried by the electric power distribution system and/or depending upon the particular construction of the surge arresting elements.

Moreover, as described above, the surge arrester 10 is assembled in the following order. First, the surge arresting elements 24, 26, 28, and 30 are

stacked between the first and second end caps 20 and 22, the stack formed by the surge arresting elements 24, 26, 28, and 30 and the first and second end caps 20 and 22 is wrapped with a fiber glass weave, and the arrester housing 32 is applied to the wrapped stack of the surge arresting elements 24, 26, 28, and 30 and the first and second end caps 20 and 22. Second, this arrangement is then secured to the mounting bracket 36. Third, the subassembly 74 is applied to the second end cap 22.

Instead, the surge arrester 10 may be assembled in any desired order. For example, the surge arresting elements 24, 26, 28, and 30 may be first stacked between the first and second end caps 20 and 22, the stack formed by the surge arresting elements 24, 26, 28, and 30 and the first and second end caps 20 and 22 may be wrapped with a fiber glass weave, and the arrester housing 32 may be applied to the stacked surge arresting elements 24, 26, 28, and 30 and first and second end caps 20 and 22. Second, the subassembly 74 may be applied to the second end cap 22.

Third, the resulting arrangement may be then secured to the mounting bracket 36.

Additionally, the first and second end caps 20 and 22 may be referred to as surge arresting elements insofar as they facilitate the surge arresting function described above.

5                   Furthermore, the plastic cup 59 may be formed of any type of electrical insulating material other than plastic.

                  Also, an electrically conductive spring, such as a spring washer, may be inserted between the second  
10                   electrically conductive washer 54 and the internal wall 58.

                  Accordingly, the description of the present invention is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the  
15                   best mode of carrying out the invention. The details may be varied substantially without departing from the spirit of the invention, and the exclusive use of all modifications which are within the scope of the appended claims is reserved.

WHAT IS CLAIMED IS:

- 1                   1. A surge arrester comprising:
  - 2                   a surge arresting element, wherein the surge
  - 3                   arresting element is arranged to conduct in the presence
  - 4                   of a surge;
  - 5                   a first end cap arranged to electrically con-
  - 6                   nect the surge arresting element to a first electrical
  - 7                   line;
  - 8                   a second end cap electrically connected to the
  - 9                   surge arresting element, wherein the second end cap forms
  - 10                  a disconnector housing; and,
  - 11                  a fault disconnector arranged to electrically
  - 12                  connect the second end cap to a second electrical line,
  - 13                  wherein the fault disconnector is arranged to disconnect
  - 14                  the surge arresting element from the second electrical
  - 15                  line in the event of a fault, and wherein the fault
  - 16                  disconnecter is housed within the disconnector housing
  - formed by the second end cap.

1                   2. The surge arrester of claim 1 wherein the  
2                   first electrical line is a power line, and wherein the  
                  second electrical line is substantially at ground.

1                   3. The surge arrester of claim 1 wherein the  
2                   first and second end caps are in electrical contact with  
                  the surge arresting element.

1                   4. The surge arrester of claim 1 wherein the  
                  surge arresting element is a metal oxide varistor.

1                   5. The surge arrester of claim 1 wherein the  
2                   second end cap has first and second ends, wherein the  
3                   first end is in electrical engagement with the surge  
4                   arresting element, and wherein the second end of the  
5                   second end cap is recessed to form the disconnecter hous-  
                  ing.

1                   6. The surge arrester of claim 5 wherein the  
2                   first end of the second end cap is in direct electrical  
                  engagement with the surge arresting element.



1                   7. The surge arrester of claim 1 further  
2                   comprising a mounting bracket arranged to support the  
3                   surge arresting element, the first and second end caps,  
                  and the fault disconnecter.

1                   8. The surge arrester of claim 7 further  
2                   comprising a fastener arranged to fasten the surge  
3                   arresting element, the first and second end caps, and the  
4                   fault disconnecter to the mounting bracket so that the  
5                   mounting bracket is clamped between the second end cap  
                  and the fastener.

1                   9. The surge arrester of claim 8 wherein the  
2                   second end cap has first and second ends, wherein the  
3                   first end is in electrical engagement with the surge  
4                   arresting element, and wherein the second end of the  
5                   second end cap is recessed to form the disconnecter hous-  
                  ing.

1                   10. The surge arrester of claim 1 wherein the  
2 surge arresting element comprises a plurality of surge  
arresting elements.

1                   11. An apparatus for arresting a surge on a  
2 power line comprising:

3                   a surge arresting element, wherein the surge  
4 arresting element is arranged to conduct in the presence  
5 of the surge on the power line;

6                   a first end cap, wherein the first end cap is  
7 arranged to electrically connect the surge arresting  
8 element to a first electrical line;

9                   a second end cap, wherein the second end cap is  
10 electrically connected to the surge arresting element,  
11 and wherein the second end cap forms a disconnecter hous-  
12 ing;

13                   an arrester housing arranged to house the surge  
14 arresting element and the first and second end caps;  
15 and,

16                   a fault disconnecter, wherein the fault  
17 disconnecter is arranged to connect the second end cap to

18       a second electrical line, wherein the fault disconnecter  
19       is arranged to disconnect the surge arresting element  
20       from the second electrical line in the event of a fault,  
21       and wherein the fault disconnecter is housed within the  
      disconnecter housing formed by the second end cap.

1               12. The apparatus of claim 11 wherein the  
      second electrical line is substantially at ground.

1               13. The apparatus of claim 11 wherein the  
2       first and second end caps are in electrical contact with  
      the surge arresting element.

1               14. The apparatus of claim 11 wherein the  
      surge arresting element is a metal oxide varistor.

1               15. The apparatus of claim 11 wherein the  
2       second end cap has first and second ends, wherein the  
3       first end is in electrical engagement with the surge  
4       arresting element, and wherein the second end of the

5           second end cap is recessed to form the disconnecter hous-  
ing.

1                   16. The apparatus of claim 11 wherein the  
2           arrester housing forms a substantially O-ring seal with  
respect to the first end cap.

1                   17. The apparatus of claim 11 wherein the  
2           first end cap has first and second ends, wherein the  
3           second end is in electrical engagement with the surge ar-  
4           resting element, and wherein the arrester housing forms a  
seal over the first end of the first end cap.

1                   18. The apparatus of claim 11 further compris-  
2           ing a mounting bracket arranged to support the surge  
3           arresting element, the first and second end caps, the  
arrester housing, and the fault disconnecter.

1                   19. The apparatus of claim 18 wherein the  
2           arrester housing is arranged to form a seal with respect  
to the mounting bracket and the second end cap.

1                   20. The apparatus of claim 18 further compris-  
2                   ing a fastener arranged to fasten the surge arresting  
3                   element, the first and second end caps, the arrester  
4                   housing, and the fault disconnecter to the mounting  
5                   bracket so that mounting bracket is clamped between the  
                  second end cap and the fastener.

1                   21. The apparatus of claim 20 wherein the  
2                   arrester housing is arranged to be wedged between the  
3                   mounting bracket and the second end cap when the mounting  
4                   bracket is clamped between the second end cap and the  
                  fastener so as to form a seal.

1                   22. The apparatus of claim 20 wherein the  
2                   mounting bracket has first and second recesses, wherein  
3                   the first recess is formed by a wall of the mounting  
4                   bracket, wherein the wall is tapered, wherein the second  
5                   recess is arranged to receive a flange of the second end  
6                   cap, and wherein the arrester housing is arranged to be  
7                   wedged between the tapered wall of the mounting bracket  
8                   and the flange of the second end cap when the mounting

9 bracket is clamped between the second end cap and the  
fastener so as to form a seal.

1 23. The apparatus of claim 18 wherein the  
2 second end cap has first and second ends, wherein the  
3 first end is in electrical engagement with the surge  
4 arresting element, and wherein the second end of the  
5 second end cap is recessed to form the disconnecter housing.  
ing.

1 24. The apparatus of claim 11 wherein the  
2 surge arresting element comprises a plurality of surge  
arresting elements.

1 25. A surge arrester comprising:  
2 arrester elements, the arrester elements being  
3 arranged to conduct in the event of a surge;  
4 an arrester housing that houses the arrester  
5 elements;  
6 a mounting bracket that supports the arrester  
7 elements and the arrester housing; and,

8                   a fastener that clamps the arrester elements  
9                   and the arrester housing to the mounting bracket so that  
10                  the arrester housing is wedged between the mounting  
11                  bracket and the arrester elements in order to form a seal  
                  for the arrester elements.

1                   26. The surge arrester of claim 25 wherein the  
2                   arrester elements comprise an end cap, wherein the end  
3                   cap has first and second ends, wherein the first end is  
4                   in electrical engagement with another of the arrester  
5                   elements, and wherein the second end of the second end  
                  cap is recessed to form a disconnecter housing.

1                   27. The surge arrester of claim 26 further  
2                   comprising a fault disconnecter, wherein the fault  
3                   disconnecter is arranged to be in electrical series with  
4                   the arrester elements, wherein the fault disconnecter is  
5                   arranged to disconnect the arrester elements from an  
6                   electrical line in the event of a fault, and wherein the  
7                   fault disconnecter is housed within the disconnecter  
                  housing formed by the end cap.

1                   28. The surge arrester of claim 25 wherein the  
2 mounting bracket has first and second recesses, wherein  
3 the first recess is formed by a wall of the mounting  
4 bracket, wherein the second recess is arranged to receive  
5 a flange of one of the arrester elements, and wherein the  
6 arrester housing is arranged to be wedged between the  
7 wall of the mounting bracket and the flange of the one  
8 arrester element when the arrester elements and the arrester housing are clamped to the mounting bracket.

1                   29. The surge arrester of claim 28 wherein the  
2 wall is tapered, and wherein the arrester housing is arranged to be wedged between the tapered wall of the  
3 mounting bracket and the flange of the one arrester element when the arrester elements and the arrester housing  
4 are clamped to the mounting bracket.

1                   30. The surge arrester of claim 28 wherein the  
2 arrester elements comprise an end cap, wherein the end  
3 cap has first and second ends and the flange, wherein the  
4 first end is in electrical engagement with another of the



5 arrester elements, and wherein the second end of the  
6 second end cap is recessed to form a disconnecter hous-  
ing.

1 31. The surge arrester of claim 30 further  
2 comprising a fault disconnecter, wherein the fault  
3 disconnecter is arranged to be in electrical series with  
4 the arrester elements, wherein the fault disconnecter is  
5 arranged to disconnect the arrester elements from an  
6 electrical line in the event of a fault, and wherein the  
7 fault disconnecter is housed within the disconnecter  
housing formed by the end cap.

1 32. The surge arrester of claim 25 wherein the  
2 arrester elements comprise an arrester block and first  
and second end caps.

1 33. The surge arrester of claim 32 wherein the  
arrester block comprises more than one arrester block.

1                   34. The surge arrester of claim 25 wherein the  
2 mounting bracket has a recess, wherein the recess is  
3 formed by a wall of the mounting bracket, and wherein the  
4 arrester housing is arranged to be wedged between the  
5 wall of the mounting bracket and one of the arrester  
elements.

1                   35. The surge arrester of claim 34 wherein the  
one of the arrester elements is an end cap.

1                   36. The surge arrester of claim 35 wherein the  
end cap houses a fault disconnecter.

1                   37. A surge arrester comprising:  
2                   a plurality of surge arresting elements, where-  
3                   in a first of the surge arresting elements is arranged to  
4                   be electrically connected to a first electrical line,  
5                   wherein a second of the surge arresting elements is ar-  
6                   ranged to conduct in the presence of a surge, and wherein  
7                   a third of the surge arresting elements forms a  
8                   disconnecter housing;  
9                   an arrester housing arranged to house the  
10                  plurality of surge arresting elements so that the  
11                  disconnecter housing is accessible from an exterior of  
12                  the arrester housing; and,  
13                  a fault disconnecter arranged to electrically  
14                  connect the third of the surge arresting elements to a  
15                  second electrical line, wherein the fault disconnecter is  
16                  arranged to disconnect the surge arresting elements from  
17                  the second electrical line in the event of a fault, and  
18                  wherein the fault disconnecter is housed within the  
                  disconnecter housing.

1                   38. The surge arrester of claim 37 wherein the  
arrester housing is a polymeric housing.

1                   39. The surge arrester of claim 37 wherein the  
arrester housing is a porcelain housing.

1                   40. A surge arrester comprising:  
2                   arrester elements, the arrester elements being  
3                   arranged to conduct in the event of a surge;  
4                   an arrester housing that houses the arrester  
5                   elements;  
6                   a mounting bracket that supports the arrester  
7                   elements and the arrester housing; and,  
8                   a threadless fastener, wherein the threadless  
9                   fastener is arranged to attach the arrester elements and  
10                  the arrester housing to the mounting bracket so that the  
11                  arrester elements and the arrester housing are supported  
by the mounting bracket.

1                   41. The surge arrester of claim 40 wherein the  
threadless fastener is a snap ring.

1                   42. The surge arrester of claim 40 wherein the  
2                   arrester elements includes an end cap, and wherein the  
3                   threadless fastener engages the end cap in order to at-  
4                   tach the arrester elements and the arrester housing to  
                  the mounting bracket.

1                   43. The surge arrester of claim 42 wherein the  
2                   end cap has a first end electrically coupled to another  
3                   of the arrester elements and a second end protruding  
4                   through the mounting bracket, and wherein the threadless  
                  fastener engages the second end of the end cap.

1                   44. The surge arrester of claim 43 wherein the  
2                   second end of the end cap has a groove, and wherein the  
3                   threadless fastener engages the groove in the second end  
                  of the end cap.

1                   45. The surge arrester of claim 44 wherein the  
                  threadless fastener is a snap ring.

1                   46. The surge arrester of claim 40 wherein the  
2                   arrester elements comprise an arrester block and first  
                    and second end caps.

1                   47. The surge arrester of claim 46 wherein the  
                    arrester block comprises more than one arrester block.

1                   48. The surge arrester of claim 46 wherein the  
2                   arrester block has first and second ends, wherein the  
3                   first end cap is electrically coupled to the first end of  
4                   the arrester block, wherein the second end cap is elec-  
5                   trically coupled to the second end of the arrester block,  
6                   and wherein the threadless fastener engages the second  
7                   end cap in order to attach the arrester elements and the  
                    arrester housing to the mounting bracket.

1                   49. The surge arrester of claim 48 wherein the  
2                   second end cap has a first end electrically coupled to  
3                   the arrester block and a second end protruding through  
4                   the mounting bracket, and wherein the threadless fastener  
                    engages the second end of the second end cap.

1                   50. The surge arrester of claim 49 wherein the  
2                   second end of the second end cap has a groove, and where-  
3                   in the threadless fastener engages the groove in the  
                    second end of the second end cap.

1                   51. The surge arrester of claim 50 wherein the  
                    threadless fastener is a snap ring.

1                   52. The surge arrester of claim 48 wherein the  
2                   arrester block comprises first and second arrester block-  
3                   s, wherein each of the first and second arrester blocks  
4                   has first and second ends, wherein the first end cap is  
5                   electrically coupled to the first end of the first ar-  
6                   rester block, and wherein the second end cap is electri-  
7                   cally coupled to the second end of the second arrester  
                    block.

1                   53. The surge arrester of claim 40 wherein the  
2                   mounting bracket has a recess, wherein the recess is  
3                   formed by a wall of the mounting bracket, and wherein the  
4                   arrester housing is arranged to be wedged between the

5 wall of the mounting bracket and one of the arrester  
6 elements when the threadless fastener attaches the ar-  
7 rester elements and the arrester housing to the mounting  
bracket.

1 54. The surge arrester of claim 53 wherein the  
2 one of the arrester elements is an end cap, wherein the  
3 end cap has a first end electrically coupled to another  
4 of the arrester elements and a second end protruding  
5 through the mounting bracket, and wherein the threadless  
6 fastener engages the second end of the end cap in order  
7 to attach the arrester elements and the arrester housing  
to the mounting bracket.

1 55. The surge arrester of claim 54 wherein the  
2 second end of the end cap has a groove, wherein the  
3 threadless fastener is a snap ring, and wherein the snap  
ring engages the groove in the second end of the end cap.

1 56. The surge arrester of claim 40 wherein the  
2 mounting bracket has first and second recesses, wherein



3       the first recess is formed by a wall of the mounting  
4       bracket, wherein the second recess is arranged to receive  
5       a flange of one of the arrester elements, and wherein the  
6       arrester housing is arranged to be wedged between the  
7       wall of the mounting bracket and the flange of the one  
8       arrester element when the arrester elements and the ar-  
      rester housing are attached to the mounting bracket.

1               57. A surge arrester comprising:  
2               arrester elements, the arrester elements being  
3       arranged to conduct in the event of a surge;  
4               an arrester housing that houses the arrester  
5       elements, the arrester housing having an integrally form-  
6       ed O-ring; and,  
7               an electrically conductive connector cooperat-  
8       ing with the integrally formed O-ring to form a seal  
9       between an interior of the arrester housing and an  
10       exterior of the arrester housing, wherein the electri-  
11       cally conductive connector is arranged to be electrically  
      coupled to one of the arrester elements.

1                   58. The surge arrester of claim 57 wherein the  
2                   electrically conductive connector has a flange forming a  
                  recess, and wherein the recess receives the O-ring.

1                   59. The surge arrester of claim 57 wherein the  
2                   arrester housing has an opening through which the  
3                   electrically conductive connector extends, wherein the  
4                   opening has first and second ends and is circumscribed by  
5                   a wall extending between the first and second ends and  
6                   defining the opening, wherein the integrally formed O-  
7                   ring is integrally formed around the wall, and wherein  
8                   the electrically conductive connector has an annular  
                  groove that receives the O-ring to form the seal.

1                   60. The surge arrester of claim 57 further  
2                   comprising a mounting bracket that supports the arrester  
                  elements and the arrester housing.

1                   61. The surge arrester of claim 60 further  
2                   comprising a fastener that clamps the arrester elements  
3                   and the arrester housing to the mounting bracket so that  
4                   the arrester housing is wedged between the mounting  
5                   bracket and one of the arrester elements in order to form  
                  a seal for the arrester elements.


1                   62. The surge arrester of claim 61 wherein the  
2                   electrically conductive connector has a flange forming a  
                  recess, and wherein the recess receives the O-ring.

1                   63. The surge arrester of claim 60 wherein the  
2                   mounting bracket has a recess, wherein the recess is  
3                   formed by a wall of the mounting bracket, and wherein the  
4                   arrester housing is arranged to be wedged between the  
5                   wall of the mounting bracket and one of the arrester  
                  elements.

1                   64. The surge arrester of claim 63 wherein the  
2                   electrically conductive connector has a flange forming a  
                  recess, and wherein the recess receives the O-ring.

1                   65. The surge arrester of claim 60 wherein the  
2 mounting bracket has first and second recesses, wherein  
3 the first recess is formed by a wall of the mounting  
4 bracket, wherein the second recess is arranged to receive  
5 a flange of one of the arrester elements, and wherein the  
6 arrester housing is arranged to be wedged between the  
7 wall of the mounting bracket and the flange of the one  
8 arrester element when the arrester elements and the arrester housing are clamped to the mounting bracket.

1                   66. The surge arrester of claim 65 wherein the  
2 wall is tapered, and wherein the arrester housing is arranged to be wedged between the tapered wall of the  
3 mounting bracket and the flange of the one arrester element when the arrester elements and the arrester housing  
4 are clamped to the mounting bracket.



2 / 4






FIGURE 2


3 / 4

**FIGURE 3**

4 / 4



**FIGURE 4**



**FIGURE 5**



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/11099

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H01T1/14 H01C7/12

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H01T H01C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 404 614 A (KOCH ROBERT E ET AL) 13 September 1983	1-4, 10-14, 16, 17, 24, 57-59
A	see column 2, line 39 - column 4, line 43; figures 1, 2	5, 6, 15, 25-27, 32, 33, 40
A	US 4 663 692 A (CAROTHERS CHARLES H ET AL) 5 May 1987	
A	US 4 734 823 A (CUNNINGHAM FRANCIS V) 29 March 1988	
A	EP 0 655 814 A (JOSLYN MFG CO) 31 May 1995	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

27 August 1998

Date of mailing of the international search report

04/09/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel: (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Bijn, E

# INTERNATIONAL SEARCH REPORT

Information on patent family members

In tional Application No

PCT/US 98/11099

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4404614 A	13-09-1983	NONE	
US 4663692 A	05-05-1987	CA 1275302 A	16-10-1990
US 4734823 A	29-03-1988	NONE	
EP 0655814 A	31-05-1995	NONE	